



8HTM-200024V

PIT MASTER LED LIGHTING TOWER

Pit Master LED Lighting Towers can save 16 to 20 metric tonnes of CO2 emissions per tower per year.





Phone (07) 4842 9800

DISCOVER OUR FULL RANGE OF LIGHTING TOWERS AT

WWW.PITMASTER.COM.AU



8HTM-200024V

PIT MASTER LED LIGHTING TOWER

The Pit Master Single Axle Hydraulic LED lighting tower has been designed to deliver the most powerful lighting, low maintenance and cost saving solution to a diverse range of industry sectors. With built-in auto start/stop, hydraulic boom and stabiliser legs, site setup can be achieved within a minimum timeframe.

TECHNICAL DATA

7 x Pit Master H-Duty PM112

69.6

Light Output 343,000 Lumens (2800W)

Tower Voltage 24V DC

dB Level

Wind Rating Cert 1635 - 110km/h Alternator 4 Pole Direct Drive Kubota Z482 **Engine** Fuel Tank Capacity 215L

Fuel Tank Hours 268hrs

Electric Rotation 340 degrees Boom Rotation Boom Hydraulic Lift/Extension

Legs

Hydraulic Operation

STANDARD INCLUSIONS

SPECIFICATIONS

Controls Electronic Controller - Auto start/stop **Engine Protection** Fail Safe Shutdown - Temp, Oil and Water

Radiator Mine Safe Radiator Cap Battery Isolation Single Pole with Lockout Start Isolation Single Pole with Lockout

MDG15 Electrical Comp As per Regulated Standards MDG41 Hydraulic As per Regulated Standards E-Stop Standard

Wheel Chocks Standard

Jump Start

Chassis/Sub Frame Hot Dipped Galvanised Mud Guards Hot Dipped Galvanised **Fuel Tank** Double Bunded

Tow Hitch 50mm Ball or 75mm Pintle Ring

Jockey Wheel Heavy Duty Swing Away

Wheel Nut Indicators Standard Fitment Fire Extinguisher 4.5kg Standard Oil Recovery Oil Evacuation Tap **Fuel Recovery** Fuel Evacuation Tap

Service Upgrades 500hr Water Separator/Filter & Sump

Cat or Anderson Plug

Height 2.470 mm Length 4,280 mm Width 1,800 mm Mast Extended Height 9.0Mtr Weight (Tare) 1,920kg



24-32 Interlink Court, Paget Mackay Queensland Email: info@pitmaster.com.au Ph. 61 7 4842 9800

